

## HANDMOTION

SCAPHOID SURGERY SCREW SHORT THREADED SCREW

## INDICATIONS

HANDMOTION short threaded screws are dedicated to fractures of small bone fragments.

.....

- Scaphoid fractures
- Carpal and metacarpal fractures Carpal and metacarpal arthrodesis

## TECHNICAL FEATURES


- Auto-compressive, self drilling and self tapping screw;
- 3 diameters : Ø2.25mm, Ø2.6mm, 3.0mm;
- Cannulated screw: 2.25 and 2.6/3.0mm cannulated screws are guided by 0.8 and 1.0mm K-wires:
- Short threaded screw : 5mm, optimal compression ;
- The cylindro-conical profile of the head allows a non-traumatic insertion of the screw into the cortical bone and optimal compression of the osteotomy, thus avoiding any risk of splitting the cortical bone;
- Sterile Packaging (Tube SOSAFE);
- Material: TA6V.



- Cylindro conical shape head screw
- Cannulated screw



Self drilling screw Self tapping screw Auto-compressive screw



- 3 diameters : Ø2.25, Ø2.6 and Ø3.0mm
- Short threaded screw: 5mm





\*Grey anodized

1101	Becompiler
H0.9IFT2.25L14-ST	Ø2.25mm self drilling, self tapping, self compressive screw - L 14mm
H0.9IFT2.25L16-ST	Ø2.25mm self drilling, self tapping, self compressive screw - L 16 mm
H0.9IFT2.25L18-ST	Ø2.25mm self drilling, self tapping, self compressive screw - L 18 mm
H0.9IFT2.25L20-ST	Ø2.25mm self drilling, self tapping, self compressive screw - L 20 mm
H0.9IFT2.25L22-ST	Ø2.25mm self drilling, self tapping, self compressive screw - L 22 mm
H0.9IFT2,25L24-ST	Ø2.25mm self drilling, self tapping, self compressive screw - L 24 mm
H0.9IFT2.25L26-ST	Ø2.25mm self drilling, self tapping, self compressive screw - L 26 mm
H0.9IFT2.25L28-ST	Ø2.25mm self drilling, self tapping, self compressive screw - L 28 mm
H0.9IFT2.25L30-ST	Ø2.25mm self drilling, self tapping, self compressive screw - L 30 mm
H0.9IFT2.25L32-ST	Ø2,25mm self drilling, self tapping, self compressive screw - L 32 mm
H0.9IFT2.25L34-ST	O2.25mm self drilling, self tapping, self compressive screw - L 34 mm



# Ø2.6mm CANNULATED SCREW\*

Ref.	Description	
14 AUSTO 01 44 0T	~~	

H1.1IFT2.6L14-ST	Ø2.6mm self drilling, self tapping, self compressive screw - L 14 mm
H1.1IFT2.6L16-ST	Ø2.6mm self drilling, self tapping, self compressive screw - L 16 mm
H1.1IFT2.6L18-ST	Ø2.6mm self drilling, self tapping, self compressive screw - L 18 mm
H1.1IFT2.6L20-ST	Ø2.6mm self drilling, self tapping, self compressive screw - L 20 mm
H1.1IFT2.6L22-ST	Ø2.6mm self drilling, self tapping, self compressive screw - L 22 mm
H1.1IFT2.6L24-ST	Ø2.6mm self drilling, self tapping, self compressive screw - L 24 mm
H1.1IFT2.6L26-ST	Ø2.6mm self drilling, self tapping, self compressive screw - L 26 mm
H1.1IFT2.6L28-ST	Ø2.6mm self drilling, self tapping, self compressive screw - L 28 mm
H1.1IFT2.6L30-ST	Ø2.6mm self drilling, self tapping, self compressive screw - L 30 mm
H1.1IFT2.6L32-ST	Ø2.6mm self drilling, self tapping, self compressive screw - L 32 mm
H1.1IFT2.6L34-ST	Ø2.6mm self drilling, self tapping, self compressive screw - L 34 mm
*Golden anodized	



# Description

H1.1IFT3.0L14-ST	Ø3.0mm self drilling, self tapping, self compressive screw - L 14 mm
H1.1IFT3.0L16-ST	Ø3.0mm self drilling, self tapping, self compressive screw - L 16 mm
H1.1IFT3.0L18-ST	Ø3.0mm self drilling, self tapping, self compressive screw - L 18 mm
H1.1IFT3.0L20-ST	Ø3.0mm self drilling, self tapping, self compressive screw - L 20 mm
H1.1IFT3.0L22-ST	Ø3.0mm self drilling, self tapping, self compressive screw - L 22 mm
H1.1IFT3.0L24-ST	Ø3.0mm self drilling, self tapping, self compressive screw - L 24 mm
H1.1IFT3.0L26-ST	Ø3.0mm self drilling, self tapping, self compressive screw - L 26 mm
H1.1IFT3.0L28-ST	Ø3.0mm self drilling, self tapping, self compressive screw - L 28 mm
H1.1IFT3.0L30-ST	Ø3.0mm self drilling, self tapping, self compressive screw - L 30 mm
H1.1IFT3.0L32-ST	Ø3.0mm self drilling, self tapping, self compressive screw - L 32 mm
H1.1IFT3.0L34-ST	Ø3.0mm self drilling, self tapping, self compressive screw - L 34 mm

\*Pink anodized

### Remark:



Our SoSafe packaging is made of a shatterproof double tube for maximally reliability. All surgical items can be safely brought from the unsterile into the sterile field.

